



P10 Puff Base

PLW - PNP - NPP

Technical Data Sheet

P10 Puff Base is designed to give puff effects with very fine details.

PLW-P10 Puff Base
PNP-P10 Puff Base
NPP-P10 Puff Base

FEATURES

- Excellent washing and abrasion fastnesses.
- Very soft hand.
- Very special effects may be obtained with combinations of other special effect inks from its own series.
- Suitable for transfer.

PRINTER'S GUIDE

Bleed Resistance	Excellent
Stencil Type	Direct, indirect, and capillary films.
Mesh	32-54 t/cm (83-137 t/in)
Preparation	40% PLW/PNP/NPP-P10 Puff Base 20% PLW/PNP/NPP-125 Extender Base 40% any white or color from its own series
Curing Information	150-160°C (302-320°F) / 1 minute However, factors such as ink film thickness, curing equipment and fabric may influence the optimum cure time.
Storage	5-30°C (41-86°F). Avoid direct sun.
Cleanup	Mineral spirits and some other non-hazardous screen washes.

* All recommendation and statements made, if any, are based on Renk Yolu Kimya's research and experience. However, since Renk Yolu Kimya has no control over the conditions of use or storage of the product sold, Renk Yolu Kimya cannot guarantee the results obtained through the use of its products. All products are sold and samples given without any representation or warranty, expressed or implied, of fitness for any particular purpose or otherwise, and upon condition that the buyer shall determine the suitability of the product for its own purpose. This applies also where protective rights of third parties involved. It does not release the user from the obligation to test the suitability of the product for the intended purpose and application.

Renk Yolu Kimya San. Tic. Ltd. Şti.

Headquarters

Cumhuriyet Cad. Baglar Sok. No:2/1
34212 Gunesli - Istanbul / Turkey

Factory

Buyuk Kilicli Yolu Cad. No:16
34570 Silivri - Istanbul / Turkey

Phone: +90.212.748 49 29 Fax: +90.212.748 49 64
info@color-way.com • www.color-way.com